

2D Scanner 2800




1D / 2D



High speed scan



Big vision



Fast decoding



Screen scan



Customized



Motion tolerance
2M/S

GENERAL FEATURES

- Low power consumption, high performance
- Comprehensive reading of all mainstream 1-D, 2-D code
- Quickly read product codes and payment codes
- Supports RS232 interface and USB interface
- Accurately read the damage code, stain code, reflective code and other special bar codes
- Self-sensing reading, scanning sensitive



2800

Specifications

Physical Characteristics

Dimensions	77.4mm x 69.3mm x 168.7mm
Weight	132g
Voltage/Current	5 VDC +/-10%@500mA

Performance Characteristics

Image(Pixels)	640 p(H) x 480 p(V)
Light Source	Aimer: 617nm red LED; illumination: 3500K white LED
Field of View	40°(H) x 31°(V)
Scan Angle	Pitch ±65° Yaw 360° Roll ±60°
Symbol Contrast	≥25%
Interface	USB, RS232
Motion Tolerance	≥2m/s
Symbologies	1D Code 128, EAN-8, EAN-13, UPC-A, UPC-E, Interleaved 2 of 5, Matrix 2 of 5, Industrial 2 of 5, Code 39, Code93, Codabar, GS1-128, MSI Plessey, Code 11, Code 32, CodaBlock F Code, GS1 DataBar, China Post, Telepen
	2D PDF417, QR Code, Data Matrix, Aztec, Maxi Code, Hanxin

User Environment

Operating Temperature	0°C ~ 50°C
Storage Temperature	-20°C ~ 60°C
Drop Resistance	Withstand drop 1.5m on concrete
Humidity	5% ~ 95%, non-condensing
Waterproof Class	IP52
Ambient Light Immunity	86,000 Lux.



2800

Specifications

Typical Depth of Field

Code 39 (3.13 mil)	50mm-100mm
Code 39 (5.13 mil)	30mm-170mm
Code 39 (20 mil)	30mm-450mm
UPC-A (13 mil)	30mm-320mm
PDF (6.88 mil)	30mm-180mm
DM (10 mil)	20mm-180mm
QR (20 mil)	20mm-300mm

Dimensions (unit: mm)

