

# SuperLead

苏州斯普锐智能系统有限公司

## 4210

### 固定扫码器

### Fixed Mount 2D Barcode Reader

迷你尺寸提供强大性能

Mini portable scanner with strong capability



独特外观设计

Unique Appearance Design

- 物体自感应
- 尺寸小-集成容易
- 高速, 全方位的条码捕捉获取
- 全面读取所有主流一维、二维码
- Object auto sense
- Industrial leading scan platform
- High speed, Omni directional scanning
- Read all mainstream 1D/2D barcodes
- 多国语言条码信息直传
- 独特的精准瞄准
- 支持RS232接口和USB接口
- 读取纸张、移动电话及电脑显示器上的任何条码
- Multiple language barcode message transfer
- Miniature -easy to integrate
- Support RS232 and USB interface
- Read barcode off cell phone screens

Physical Characteristics		
尺寸Dimensions:	48mm x 40mm x 22mm	
重量Weight:	65.8g	
电压Voltage:	5 VDC	
功耗Power:	2.3W MAX	
外壳防护Ingress Protection:	IP54	
外壳材质Material:	PC +ABS	
Performance Characteristics		
传感器Image :	640 pixels (H)x 480 pixels (V) 全局快门 60FPS	
光源Light Source:	Illumination:RED LED	
接口支持Interfaces Supported:	USB2.0, RS232	
Symbology Decode Capability		
一维条码/1-D:	UPC, EAN, IAN, Code 128, Code 39, Code 93, Industrial 2 of 5 Interleaved 2 of 5.etc	
二维条码/2-D:	PDF417, Data Matrix, QR Code, Aztec .etc	
User Environment		
工作温度Operating Temperature:	0°C to 50°C	
存储温度Storage Temperature:	-20°C to 70°C	
湿度Humidity:	0% to 95% relative humidity,non-condensing	
抗震性Shock Specifications:	Designed to withstand 1.2m(5' ) drops	
环境光免疫Ambient Light Immunity:	0-100,000 Lux.	
Decode Ranges		
角度	42°	70°
6.88mil PDF	25mm-150mm	10mm-80mm
10mil DM	25mm-145mm	15mm-80mm
13mil UPC-A	45mm-260mm	20mm-160mm
20mil QR	35mm-285mm	10mm-170mm
20mil C39	50mm-400mm	20mm-235mm
Febreban	140mm-225mm	70mm-120mm
Performance may be impacted by bar code quality and environmental conditions		
   		